

WAY PURE® 68

DESCRIPTION

Way-Pure® 68 is the first coolant friendly way oil option available.

Way-Pure® 68 waylube is a premium blend of highly refined lubricating oils and a non-corrosive, anti-wear extreme pressure package specifically designed to provide maximum lubricity and long service life.

Way-Pure® 68 waylube does not contain conventional extreme pressure additives such as phosphorous, zinc and sulfur and thus will not contribute to the premature degradation of metalworking fluid systems.

Way-Pure® 68 waylube is the cost-effective product of choice when the application calls for an environmentally friendly, premium, anti-wear, long life, way oil with an ISO grade of 68.

Way-Pure® 68 waylube meets the requirements of Cincinnati Milacron specifications P-47.

PRODUCT CHARACTERISTICS

Appearance:	Amber
Viscosity:	61.2 – 74.8 cSt @ 40°C
Stick Slip Test:	0.08
Density:	7.33 lbs/gal

Revision 3

**OTHER SPECIFIC BENEFITS OF WAY-PURE® 68
INCLUDE:**

- ELIMINATES “MONDAY MORNING ODOR”
- REDUCES COOLANT CONSUMPTION, BIOCIDES USE AND REDUCES COOLANT COSTS
- KEEPS WAY OIL MANIFOLDS, LINES, CHECK VALVES, AND INJECTORS CLEAN
- INCREASES PRODUCTION
- ENVIRONMENTAL FRIENDLY
- INCREASES WORKER SAFETY AND SATISFACTION
- COST EFFECTIVE
- WORKS WITH ALL QUALITY COOLANTS

Way Oil Equivalent Chart

CONDAT	WAY-PURE® 68
Mobil	Vactra #2
Shell	Tonna V 68
Texaco	Way Lubricant 68
Sun	Way Lubricant 1180
Chevron	Vistac Oil 68X
Amoco	WayTac 68
Kendall	Way Oil #10
Exxon	Febis K 68
Ashland	WayLube 68
Citgo	Amplex 28 P
Arco	Truslide S-150
Gulf	Gulfway 68
Noco	Waylube 68

Revision 3