

Hydra-Pure[®] 2032 AW Phosphorous & Zinc Free Hydraulic Oil

DESCRIPTION

Hydra-Pure 2032 AW is a premium ISO-32 grade anti-wear, rust and oxidation inhibited hydraulic oil blended from a high quality paraffinic distillate base stock. The exclusive patented, anti-wear and anti-oxidant package is specifically designed to provide maximum lubricity, long service life and superior system cleanliness.

Hydra-Pure 2032 AW also provides the additional benefit of extending the service life of soluble oil coolants by eliminating the presence of zinc and phosphorous due to leaking of hydraulic oils into circulating systems.

Hydra-Pure 2032 AW contains selected demulsifiers and anti-foaming agents to provide rapid release of water and entrained air.

Hydra-Pure 2032AW is the product of choice whenever the application calls for a premium, anti-wear, long life hydraulic oil with an ISO grade of 32, and there is an environmental concern caused by the presence of zinc and \ or phosphorous.

PRODUCT CHARACTERISTICS

Appearance: Amber

Viscosity: 28.8 – 35.2 cSt @ 40°C

APPLICATIONS

Hydra-Pure 2032 AW hydraulic oil is designed to be used in applications which require extreme pressures in the operating system as well as those systems continuously exposed to adverse conditions such as corrosion and contamination.

Revision 1